

# 



**Flexible** *One System For All Sites*

**Simple** *Minimum Operating Skill*

**Efficient** *High Capacity with Less Cost*

## **FLEXI** Membrane Filtration System Technical Spec Model : FLEXI-MF2.5

1	Membrane Dimension : 8" diameter x 63" Length
2	Membrane Material : Modified Hydrophilic Polymer
3	Configuration : Capillary Type, Out to in Filtration
4	Recovery Ratio : 90% - 99%
5	Max Operating Pressure : 0.5-1.5 bar
6	Max Operating Temp : 40°C
7	Filtration Rating : 01 -0.01micron
8	Filtration Quality : <0.2 NTU
9	Filtrate SDI : <3
10	Feed Turbidity : <20 NTU
11	Flush Type : Automated Back Wash
12	Operation : Automated Control Switch

## ***Sales & Service Support***

Flexi's qualified personnel will off customized design, installation, operation and maintenance training according to your specific requirements.

For further enquiry, please contact

### **FLEXI SYSTEMS (SINGAPORE) PTE LTD**

No. 397A, Woodlands Road, Singapore 677995

Tel: (65) 6468 9008 Fax: (65) 6759 2565

Email: sales@flexisystems.com.sg

Website: www.flexisystems.com.sg